

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-8. (Canceled)

9. (Currently amended) A shears device, comprising:
- a rolling table having a movable part;
  - a rail-guided drive carriage coupled with the movable part of the rolling table;
  - a U-shaped frame incorporating a vertical base and two horizontal arms that make the frame U-shaped, the arms having first and second sides, the first sides of the arms being connected to the vertical base, the U-shaped frame being mounted on the drive carriage;
  - a transport line extending through the horizontal arms;
  - shears;
  - a drive apparatus arranged on the drive carriage for driving the shears;
  - the shears arranged on the U-shaped frame, the ~~frame having a~~

first side of the arms being adjacent the drive apparatus and the a second side of the arms being opposite the first side; holding elements provided on the first side and the second side of the arms;

blade holders supported by the holding elements, the shears being supported by the blade holders, wherein ~~at least one of~~ the holding element ~~elements~~ on the second side of an upper of the horizontal arms has ~~comprises~~ at least one pressure plate;

a drive for moving the drive carriage transverse to the transport line while a ~~the~~ work piece is positioned in the transport line;

a clamping element arranged adjacent ~~at~~ the second side of the arms ~~frame~~, the clamping element having congruent gliding plates that overlap the at least one pressure plate; and wherein the clamping element together with the gliding plates is movable along a horizontal path across the at least one pressure plate so that the clamping element and the at least one of the holding elements are coupled.

10. (Currently amended)            A shears device, comprising:
- a rolling table having a movable part;
- a rail-guided drive carriage coupled with the movable part of

the rolling table;

a U-shaped frame incorporating a vertical base and two horizontal arms that make the frame U-shaped, the arms having first and second sides, the first sides of the arms being connected to the vertical base, the U-shaped frame being mounted on the drive carriage;

a transport line extending through the horizontal arms;

shears;

a drive apparatus arranged on the drive carriage for driving the shears;

the shears arranged on the U-shaped frame, ~~the frame having a~~ first side of the arms being adjacent the drive apparatus and the a second side of the arms being opposite the first side; holding elements provided on the first side and the second side of the arms;

blade holders supported by the holding elements, the shears being supported by the blade holders, wherein ~~at least one of~~ the holding element ~~elements~~ on the second side of an upper of the horizontal arms has threaded spindle coupling rods connected so as to be pivotable to both the first side and the second side of the arms frame, the ~~which~~ coupling rods are pivotable through recesses in the drive carriage so as to engage in congruent coupling sockets of a lower of the

horizontal arms or in congruent coupling sockets of the holding element on a upper of the arms;  
a drive for moving the drive carriage transverse to the transport line while a ~~the~~ work piece is positioned in the transport line; and  
a force means for pivoting ~~moving the coupling rods to~~  
~~generate a coupling between~~ the coupling rods into contact  
with one of said ~~and the~~ coupling sockets.

11. (Currently amended)           A shears device, comprising:  
a rolling table having a movable part;  
a rail-guided drive carriage coupled with the movable part of the rolling table;  
a U-shaped frame incorporating a vertical base and two horizontal arms that make the frame U-shaped, the arms having first and second sides, the first sides of the arms being connected to the vertical base, the U-shaped frame being mounted on the drive carriage;  
a transport line extending through the horizontal arms;  
shears;  
a drive apparatus arranged on the drive carriage for driving the shears;  
the shears arranged on the U-shaped frame, the ~~frame having a~~

first side of the arms being adjacent the drive apparatus and the a second side of the arms being opposite the first side; holding elements provided on the first side and the second side of the arms;

blade holders supported by the holding elements, the shears being supported by the blade holders;

a drive for moving the drive carriage transverse to the transport line while a ~~the~~ work piece is positioned in the transport line;

a clamping element correlated transversely to the two horizontal frame arms, the clamping element is configured to pivot about a pivot joint, wherein the ~~being arranged to fold upwardly through a joint having a pivot axis of the pivot joint that~~ extends parallel to the transport line; and a ~~force~~ means for pivoting the clamping element between a position wherein the clamping element couples ~~coupling~~ the two horizontal ~~frame~~ arms and a position wherein the coupling element does not couple ~~releasing the coupling of~~ the two horizontal ~~frame~~ arms.

12. (New) The shears device according to claim 10, wherein the contact between the rods and the sockets is form-fit/frictional contact.